

Deneb Suspended

Fitting available in Suspended, Surface and Recessed Mount

A LED luminaire with added LGP (Light Guide Panel) technology well suited for indoor lighting solutions. The Luminaire is suitable for surface and suspended mounting.



Luminaire details for specification code:

R-DENA-25-3080-C-02-SO

(see table below for full variants)

Fitting Type:	Suspended	Power:	198-264 VAC voltage, 176-276 VDC voltage
IP Rating:	IP20	MacAdams Step:	3 or better
COB Lumen Output:	3644	UGR:	UGR<19
Actual Lumen Output:	2842	Emergency:	3 hours
Watts:	25	Lifetime:	L80 > 60000h
Lumen Efficacy (lm/W):	114	Warranty:	5 Years
Typical Emergency Lumens:	464	Diameter (mm):	595 x 595 x 49 mm

Specification Codes for Deneb Suspended

Reality Series-Deneb-Suspended-25 Watts-3000K 80CRI-Non-Dim-white-Slim opal

Range	Product	Size/Power	CCT	Beam Angle	Dimming	Main Colour	Secondary Colour (if applicable)	Accessories	Emergency
R	DENA	/25	3080		C	02		SO	EM
Reality Series	Deneb	DEN / 25, 36 or 41	3000K / 80 CRI 4000K / 80 CRI		A / DALI C / Non-Dim	01 / Black 02 / White 03 / Grey 05 / Granite Grey		SO/ Slim opal or SP/ Slim prism	Leave EM off your code if you do not require emergency kit

GDS Reality Series DENA Square Suspended 595mm 3000K 25W Slim Opal / LDC (Polar)

Luminaire: GDS Reality Series DENA Square Suspended 595mm 3000K 25W Slim Opal
Lamps: 4 x LED

